

Bronchovideoscope  
**BF-H1200**

Going beyond the 5 mm Diameter Barrier with Native HDTV Image Quality





## 4.9 mm Diameter with HDTV Image Quality


Thanks to the incorporation of a newly developed micro image sensor, we were able to create a new HDTV compatible diagnostic bronchoscope with an outer diameter of less than 5.0 mm.

## Advanced Suction Capability

Even more impressively, this slim scope comes with a bigger 2.2 mm instrument channel plus greater suction capability compared to the 2.0 mm instrument channel diameter of its predecessor.<sup>1</sup>

## Excellence in Ease of Use

Based on technologies which made its predecessor a highly valued tool in bronchoscopy, the BF-H1200 features a rotatable insertion tube that turns 120° in either direction for easier targeting and delivery or withdrawal of EndoTherapy devices.<sup>1</sup> A waterproof one touch connector enables quicker connection of the endoscope to the system.



## Observation Modes

### TXI (TeXture and color enhancement Imaging)<sup>2</sup>

Delivering a new ease and clarity of observation by utilizing brightness, tissue texture and color differentiation. Bronchoscopy is enhanced by a combination of brightness correction of the dark image areas and an accentuation of the observed tissue texture.

### NBI (Narrow Band Imaging)<sup>3</sup>

The proven imaging technology helps physicians to inspect suspicious lesions. During endoscopic observation, NBI enhances the visualization of the capillary network and mucosal morphology.

### RDI (Red Dichromatic Imaging)<sup>2</sup>

Enhances the visualization of vessels in deeper layers of the mucosa. By using narrow bands of the red part of the light spectrum (long wavelength bands of 600 nm and 630 nm) which penetrate deeper into the mucosa, deep vessels can be displayed in stronger contrast and hence are better visualized.

<sup>1</sup> Olympus EVIS LUCERA ELITE BF-H290/Q290 bronchovideoscopes

<sup>2</sup> Requires EVIS X1 CV-1500 video system center

<sup>3</sup> Requires EVIS X1 CV-1500, CV-190 or CV-190 Plus video system center

Specifications		
<b>Optical System</b>	Field of view	120°
	Direction of view	Forward viewing
	Depth of field	3-100 mm
<b>Insertion Tube</b>	Distal end outer diameter	4.9 mm
	Distal end enlarged	
	Insertion tube outer diameter	4.9 mm
	Working length	600 mm
	Insertion tube rotation function	Yes
<b>Instrument Channel</b>	Channel inner diameter	2.2 mm
	Minimum visible length	3.0 mm from the distal end
	Direction from which EndoTherapy accessories enter and exit the endoscopic image	
<b>Bending Section</b>	Angulation range	Up 210° / Down 130°
<b>Electrocautery Instrument Compatibility</b>		Yes
<b>Laser Compatibility</b>		Nd:YAG
<b>Compatible Systems</b>		Olympus EVIS X1 CV-1500 video system center Olympus EVIS LUCERA ELITE CV-290 video system center Olympus EVIS LUCERA ELITE CLV-290SL, CLV-290 xenon light source



Olympus BF-H1200 bronchovideoscope

Olympus reserves the right of errors, modification and changes of the service and/or product offerings.